

Non-contractual picture



- PNR 122 Jurop (12200 l/min)
- Sprung drawbar
- Air brakes (BPW axles)
- Wheels: 650/65R26.5
- Self steering axle
- Pre-equipment for hydraulic mixer
- Pre-equipment for Jumbo pumping arm (Ø 200 mm)
- Pre-equipment for hydraulic trap

Standard equipment KOMFORT2

- | | |
|--|--|
| <ul style="list-style-type: none"> ✓ Manufactured in special steel (55 kg) ✓ Tank galvanized inside and outside ✓ Manufactured according to norms EN707 and CE/97/23 ✓ 2 half-circular indicators (Ø 2") ✓ Overpressure security (Ø 6") ✓ Anti-spill valve (pump security) ✓ Self-cleaning syphon (30 l) ✓ Pressure gauge (Ø 100 mm) ✓ 6-spline Walterscheid P.T.O.-shaft ✓ 3 flanged outlets: left and right, and left on the rear wall ✓ 4 m of Ø 6" PVC pipe (see page 24 of the general price list for other kinds of pipes) ✓ Rear manhole (Ø 600 mm) ✓ Rear hydraulic valve (Ø 6") (SA) | <ul style="list-style-type: none"> ✓ Perrot couplings ✓ Exact scatterer ✓ Recessed lighting ✓ Bolted fixed eyelet ✓ Galvanized universal chassis (pre-equipment for rear implement), Ø 8" draining cap with quick opening (stone trap) underneath the tank ✓ Adjustable bolted running gear (adjustable position) ✓ Air braking system with double circuit ✓ Drawbar with cross-springs ✓ Low hitching ✓ Double truck-type lights ✓ JOSKIN Roll-Over boggie with 1600 mm parabolic leaves ✓ Galvanized mudguards instead of hose carrying hooks ✓ BPW axles: 150-10S with 410x180 mm brakes |
|--|--|

Specific equipment Win Pack K16003

- | | |
|---|---|
| <ul style="list-style-type: none"> • 0307D • 1936 x 2 • 680 • 899 • 317 • 936 • 1326 • 050 • 173 • 110 • 012 | <ul style="list-style-type: none"> Slurry tanker KOMFORT 2 16000 TS Type Germany Wheels 650/65R26.5 (Alliance) 174D TL I 380 (Ø 1518 x 664 mm, 6080/9110 kg per wheel at 40 km/h) 1700 mm boggie leaves and leaf guide instead of standard (COMPULSORY for wheel Ø from 1406 to 1600 mm - forbidden with fixed axles) Self steering axle with hitching yoke - including quick coupling to the tractor - and aligning set-up unit including 2 nitrogen balls, oil tank, hand pump and pressure gauge Braking power in proportion to the load on air brakes with level float gauge Flashing beacon Pump type PNR 122 JUROP (12.200 l/min at atmospheric pressure - 11.200 l/min at 60 % vacuum) - 540 rpm speed-increasing gearbox - with automatic lubrication, Ø 150 mm JOSKIN pressure relief valve and air injection cooling instead of MEC 8000 Hydraulic control of pump change over (DA) ECOPUMP: special large volume exhaust pipe with oil collector, high air intake and noise level reduction 6-spline wide-angle Walterscheid P.T.O.-shaft (1 side) Ø 6" communicating gauge instead of Ø 2" half-circular indicator on front wall |
|---|---|

WIN *PACK*
WPK 16003

JOSKIN

Slurry tanker KOMFORT2 16000 TS

- 015 x 2 Ø 8" flanged outlet instead of standard 6" (left and right on the front)
- 097 Pre-equipment for not built-in front JUMBO (Ø 200 mm)
- 896 Pre-equipment for hydraulic mixer
- 1865 Pre-equipment for hydraulic trap (500 x 600 mm) - including pre-equipment for inner and outer ladders