

Non-contractual picture



- MEC 6500 (6500 l/min)
- Rigid drawbar
- Hydraulic brakes
- Wheels: 550/60-22.5
- Pre-equipment for air mixer

Standard equipment MODULO2

- | | |
|---|--|
| <ul style="list-style-type: none"> ✓ Manufactured in special steel (55 kg) ✓ Tank galvanized inside and outside ✓ Manufactured according to norms EN707 and CE/97/23 ✓ 2 half-circular indicators (Ø 2") ✓ Overpressure security (Ø 6") ✓ Anti-spill valve (pump security) ✓ Self-cleaning syphon (30 l) ✓ Pressure gauge (Ø 100 mm) ✓ 6-spline Walterscheid P.T.O.-shaft ✓ 3 flanged outlets: left and right, and left on the rear wall ✓ 4 m of 6" PVC pipe (see page 24 of the general price list for other kinds of pipes) | <ul style="list-style-type: none"> ✓ Hose carrying hooks on both sides ✓ Rear manhole (Ø 600 mm) ✓ Rear hydraulic valve (Ø 6") (SA) ✓ Perrot couplings ✓ Exact scatterer ✓ Recessed lighting ✓ Bolted fixed eyelet ✓ Adjustable bolted running gear (adjustable position) ✓ Hydraulic brakes ✓ Rigid drawbar ✓ Low hitching |
|---|--|

Specific equipment Win Pack M6002

- | | |
|---|--|
| <ul style="list-style-type: none"> • 0215 • 2045 • 039 • 025 • 344 • 1946 | <ul style="list-style-type: none"> Slurry tanker MODULO 2 6000 ME with rigid drawbar Wheels 550/60R22.5 16 PR Flot 648 (BKT) TL-648 (Ø 1230 x 550 mm, 5450 kg per wheel at 40 km/h) Pump: 6500 (MEC 6500) BP instead of 5000 (MEC 5000) Ø 6" filling valve with Perrot rocking jaw Pre-equipment for air mixer Manual parking brake mounted on the drawbar |
|---|--|