

Non-contractual picture



- TÜV equipment - Germany
- Drawbar with cross-springs
- Air brakes (braking power in proportion to the load)
- Wheels: 650/55R26.5
- Self steering axle
- Hydro-Tandem with 1800 mm wheel base
- Large sight window with rods and perspex closing plate (177 x 76 cm)

Standard equipment Trans-SPACE

- | | |
|---|---|
| <ul style="list-style-type: none"> ✓ Tapered monocoque body ✓ 4 mm floor in 400 HB hard wearing steel, 4 mm side sheets + upper strip in HLE 550 ✓ Outer hooks to hang a cover ✓ Optional extensions ✓ Galvanized front ladder ✓ Tubular chassis (300 x 100 x 10 mm) ✓ Chassis width: 900 mm ✓ BPW axles: 2 x 150 x 2100 - 10S ✓ Air brakes (410 x 180 mm) ✓ Bolted fixed eyelet ✓ Hitching cross-suspension with parabolic leaves ✓ 1-part hydraulic door (DA) | <ul style="list-style-type: none"> ✓ Central grain chute (500 x 500 mm) ✓ Hydraulic skid with direct connection to the tractor (DA) ✓ Opening function and hydraulic skid connected to one single distributor with manual 6-way valve ✓ Oil fed tipping ✓ Double oscillating frame for tipping cylinder ✓ Galvanized and bolted mudguards ✓ Double truck-type lights ✓ Shot-blasting before painting ✓ Primer Ester Epoxy (2 K) + finishing lacquer (2 K) (total 100µ) ✓ Forced drying (60° oven) ✓ Pre-equipment platform |
|---|---|

Specific equipment Win Pack TS7007

- | | |
|---|---|
| <ul style="list-style-type: none"> • 4630D • 396 x 2 • 1465 • 1775 • 899
 • 114 • 428 • 1466 • 1850 • 1761 • 1448 • 1445 • 1973 | <ul style="list-style-type: none"> Monocoque tipping trailer Trans-SPACE 7000/23BC150 Type Germany Wheels 650/55R26.5 (Alliance) 167 E TL380 (Ø 1360 x 645 mm, 6000/7900 kg per wheel at 40 km/h) Hydro-Tandem: hydraulic axle suspension (DA) (triple axle type) Wheel base: 1820 mm instead of 1550 mm with Hydro-Tandem and Hydro-Tridem Self steering axle with hitching yoke - including quick coupling to the tractor - and aligning set-up unit including 2 nitrogen balls, oil tank, hand pump and pressure gauge Braking power in proportion to the load on air brakes with Hydro-Tandem Thermoplastic mudguards Tipping stabilizer with Hydro-Tandem or Hydro-Pendul - electric control Scharmüller bolted eyelet (Ø 80 mm) (large plate) instead of Rockinger eyelet Cylinder: 41 l instead of 65 l Lateral lights and side lights (4 lights) Flashing beacon on lighting Large front sight window with galvanized rods and transparent perspex plate (177 x 76 cm) |
|---|---|