

# JOSKIN

## ADVANTAGE SERIES

### VOLUMETRA 16500 + ARTICULATED ARM

ADV16500V/2-20



Non-contractual photo

**ADVANTAGE** SERIES

- ✓ VOLUMETRA 16,500 l slurry tanker
- ✓ Structure with integrated chassis made of special steel, galvanised inside and outside
- ✓ Hydropneumatic drawbar with 2 nitrogen accumulators (suspension when vehicle loaded and unloaded)
- ✓ JOSKIN Ø 80 mm 4 t knee-joint eyelet (large plate)
- ✓ Hydro-Tandem running gear with ADR 150 axles and 420 x 180 mm brakes
- ✓ Rear self-steering axle with K50 knee-joint eyelet, including quick coupling to the tractor and aligning set-up unit
- ✓ Wheels 750/60R30.5 A389VF (Alliance) 183D (Ø 1,680 x 780 mm, 11,640 kg per wheel at 40 km/h and 4 bar)
- ✓ Air brakes in proportion to the load
- ✓ JURUP PN 155 pump (15,200 l/min at atmospheric pressure - 13,217 l/min at 60% vacuum) - 1,000 rpm - with hydraulic reverser
- ✓ Wide angle P.T.O.-shaft (1 side) (Walterscheid)
- ✓ High-flow turbo-filler (Ø 200 mm) on filling arm
- ✓ ECOPUMP: special large volume exhaust pipe with oil collector, high air intake and noise level reduction
- ✓ Self-supporting filling arm (Ø 200 mm) on the right side with elbow (to pump in off-ground pits) and orientation by hydraulic motor
- ✓ Control automaton (2+4) for the automatic control of the spreading implements
- ✓ Complete pre-equipment for spreading implement, including integrated linkage with suspension
- ✓ Isobus control with electronic flow meter + joystick with 23 functions
- ✓ Pre-equipment for tyre inflation system
- ✓ 2 LED working lights at the back (with control box in the cabin), flashing beacon and LED side marker lights
- ✓ European certification for 24-t max. GVW (20 t on axles + 4 t on eyelet) at 40 km/h



**Other Advantage series on:**  
[www.joskin.com/advantage](http://www.joskin.com/advantage)