



JOSKIN is already offering various models of covers for its agricultural trailers. In order to complete this range, we add the Telecover to the available options.

The loading of some products (e.g. potatoes) requires a wide upper access to the trailer. The design of the Telecover - without roll bar inside the body - makes it an ideal cover for this kind of work.

Available on monocoque tipping trailers and multi-purpose trailers, this strong cover (690 g/m²) is hydraulically operated from the tractor. All handling works (climb, unwind, put straps, etc.) are now unnecessary. In short: safer, faster and more productivity!

When opening, the Telecover winds around a longitudinal axis driven by a hydraulic motor. Two articulated arms (at the front and at the back of the body) ensure the move along of the axis from left to right and inversely for closing. This system (which is watertight) allows to open the door even when the cover is closed. A point on which JOSKIN devoted a particular attention is the suppression of any wind resistance when opening or closing the cover. The articulations of the two arms allow to move laterally the winding axis without raising it up.



Non contractual data, likely to change.

ADVANTAGES of the Telecover cover:

- no roll bar in the body;
- watertight covering system;
- hydraulic drive;
- low air resistance;
- suited to all products, even if the load is not flat.

An explanatory **video** available on <https://www.youtube.com/user/JoskinSA>.

Ref.	Designation
5325	TELECOVER cover with hydraulic control (DA) for bodies from 8000 to 9600 (with structure to open door as the cover is closed - winding on the right) - net price for customer



Door can be opened even when the cover is closed

Non contractual data, likely to change.